


F6 Two-way Radio



1 F6-EM earphone / clip microphone

2 F6-HM hand microphone

3 Charger

TECHNICAL DATA		F6	FEATURES	
RF output power		0.5 W	<ul style="list-style-type: none"> · Clear audio quality · Automatic noise reduction · TOT Time-out timer to stop transmitting automatically · Monitoring function · DCS/CTCSS encoder and decoder prevents interference in the same frequency · Housing made of die-cast and high-resistant plastic · Powerful lithium polymer rechargeable battery · Battery saving mode · Channel annunciation in English language · LED shows receipt, transmission and battery status · European wide licence and toll-free usable · PC programmable (optional): · Frequency, functions and settings can be set by the optional programming software 	
Frequency range		446.000 – 446.100 MHz		
Channels		16		
Audio output		1 W		
Accu / operating time		12 V Li-Po 1300 mAh / 12 h – 30 h		
Temperature range		-25 °C to +55 °C		
Dust / water protection		IP 54		
Shock / vibration		MIL STD 810 C/D/E & TIA/EIA 603		
Working ranges				
outside, open terrain		5 km		
outside, area between buildings		3 km		
OPTIONAL ACCESSORIES		OPTIONAL ACCESSORIES	SUPPLIED WITH	
F6-HM MICROPHONE		F6-EM EARPHONE	ART.-NO. 870000	
ART.-NO. 870100		ART.-NO. 870150	<ul style="list-style-type: none"> · Two-way radio · Rechargeable battery · Charger · Belt clip · Hand strip 	
<ul style="list-style-type: none"> · F6-HM hand microphone with jacket clip 		<ul style="list-style-type: none"> · F6-EM earphone / clip microphone 		